

Safety Data Sheet

Micro-Sorb® 8/16 LVM

Revision date : 2010/08/16
Version: 2.0

Page: 1/7
(30289230/SDS_GEN_US/EN)

1. Product and Company Identification

Use: {**[E]BAS01-**}

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Synonyms: Attapulgite Clay

2. Hazards Identification

Emergency overview

CAUTION:

May cause cancer by inhalation.
The International Agency for Research on Cancer (IARC) has classified this substance as group 3, not classifiable as to its carcinogenicity to humans.
Prolonged and repeated exposure of dust may cause lung damage.

State of matter: solid
Colour: tan
Odour: odourless

Potential health effects

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Virtually nontoxic after a single ingestion.

Irritation / corrosion:

Contact with powders or dusts may irritate the eyes, skin and respiratory tract.

Chronic toxicity:

Carcinogenicity: The International Agency for Research on Cancer (IARC) has classified this substance as group 3, not classifiable as to its carcinogenicity to humans. This product contains crystalline silica (quartz).

Repeated dose toxicity: NIOSH has studied the exposure effects of Attapulgite, which contains crystalline silica, on pulmonary function and has determined that there is no evidence of significant respiratory morbidity.

Safety Data Sheet

Micro-Sorb® 8/16 LVM

Revision date : 2010/08/16
Version: 2.0

Page: 2/7
(30289230/SDS_GEN_US/EN)

Potential environmental effects

Aquatic toxicity:

At the present state of knowledge, no negative ecological effects are expected.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
8031-18-3	90.0 - 99.0 %	Fuller's earth
14808-60-7	1.0 - 10.0 %	crystalline silica

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

If on skin:

Wash thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Seek medical attention if necessary.

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Flash point:

Non-flammable.

Suitable extinguishing media:

dry powder, foam

Unsuitable extinguishing media for safety reasons:

carbon dioxide

Hazards during fire-fighting:

No particular hazards known.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

Safety Data Sheet

Micro-Sorb® 8/16 LVM

Revision date : 2010/08/16
Version: 2.0

Page: 3/7
(30289230/SDS_GEN_US/EN)

6. Accidental release measures

Personal precautions:

Avoid dust formation. Avoid prolonged inhalation. Ensure adequate ventilation. Use personal protective clothing.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

Avoid raising dust.

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Contain with dust binding material and dispose of.

7. Handling and Storage

Handling

General advice:

Ensure adequate ventilation. Avoid dust formation. Avoid contact with skin and eyes. See American Society for Testing and Materials (ASTM) Standard Practice E1132-99a, 'Standard Practice for Health Requirements Relating to Occupational Exposure to Respirable Crystalline Silica.'

Protection against fire and explosion:

No special precautions necessary.

Storage

General advice:

Keep container tightly closed and dry; store in a cool place.

Storage stability:

Contents are stable at room temperature.

8. Exposure Controls and Personal Protection

Components with workplace control parameters

crystalline silica	OSHA	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.1 mg/m3 Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.3 mg/m3 Total dust ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.
	ACGIH	TWA value 0.025 mg/m3 Respirable fraction ;

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Safety Data Sheet

Micro-Sorb® 8/16 LVM

Revision date : 2010/08/16
Version: 2.0

Page: 4/7
(30289230/SDS_GEN_US/EN)

Hand protection:
Chemical resistant protective gloves

Eye protection:
Safety glasses with side-shields.

General safety and hygiene measures:
Handle in accordance with good industrial hygiene and safety practice. In order to prevent contamination while handling, closed working clothes and working gloves should be used.

9. Physical and Chemical Properties

Form:	powder	
Odour:	odourless	
Colour:	tan	
pH value:	8 - 9.5	
Melting point:	> 1,000 °C	
Relative density:	1	
Bulk density:	304 - 737 kg/m3	
Solubility in water:		insoluble

10. Stability and Reactivity

Conditions to avoid:
Caution: Calcined Attapulgite products are sold at 1%-9% free surface moisture depending on the grade. In contact with turpentine, vegetable oil and other unsaturated organic compounds, heat may be generated when the Attapulgite is at uncommonly low free moisture levels.

Substances to avoid:
vegetable oils, unsaturated organic compounds

Hazardous reactions:
No hazardous reactions when stored and handled according to instructions.
The product is chemically stable.

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological information

Acute toxicity

Dermal:

No data available concerning acute toxicity.

Irritation / corrosion:

Eye:

Information on: crystalline silica

May cause slight but temporary irritation to the eyes.

Repeated dose toxicity

Information on: crystalline silica

Safety Data Sheet

Micro-Sorb® 8/16 LVM

Revision date : 2010/08/16
Version: 2.0

Page: 5/7
(30289230/SDS_GEN_US/EN)

Assessment of repeated dose toxicity:

This product may contain greater than 0.1% crystalline silica. Repeated exposure to high concentrations results in silicosis, a lung disease characterized by coughing, difficult breathing, wheezing, scarring of the lungs, and repeated, non-specific chest illnesses.

Carcinogenicity

Information on: crystalline silica

The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

NTP listed carcinogen

Other Information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological Information

Degradability / Persistence Biological / Abiological Degradation

Evaluation: Inorganic product which cannot be eliminated from water by biological purification processes.

13. Disposal considerations

Waste disposal of substance:

Dispose of in a licensed facility. Do not discharge into drains/surface waters/groundwater. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in a licensed facility. Empty containers or liners may retain product residues. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport USDOT

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

Safety Data Sheet

Micro-Sorb® 8/16 LVM

Revision date : 2010/08/16
Version: 2.0

Page: 6/7
(30289230/SDS_GEN_US/EN)

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US released / listed

OSHA hazard category: IARC 1, 2A or 2B carcinogen; NTP listed carcinogen; Chronic target organ effects reported; OSHA PEL established; ACGIH TLV established

EPCRA 311/312 (Hazard categories): Chronic;

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	14808-60-7	crystalline silica

CA Prop. 65:
THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

16. Other Information

HMIS III rating

Health: 1⁺ Flammability: 0 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MSDS Prepared by:
BASF NA Product Regulations
msds@basf.com
MSDS Prepared on: 2010/08/16

Micro-Sorb is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR

Safety Data Sheet

Micro-Sorb® 8/16 LVM

Revision date : 2010/08/16

Page: 7/7

Version: 2.0

(30289230/SDS GEN_US/EN)

TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Due to the merger of Engelhard Corp. and BASFGroup all Material Safety Data Sheets have been reassessed on the basis of consolidated information. This may have resulted in changes of the Material Safety Data Sheets. In case you have questions concerning such changes please contact us under the address mentioned in Section I.

END OF DATA SHEET