These breathers are designed to filter out particles and block water in its liquid state from entering fluid containing reservoirs. The B8-S8-35 offers the added feature of an oil coalescing layer to prevent oil mist from entering the work environment.

Provides the ideal solution for low humidity applications; continuous operations with frequent washdowns; and arid, high dust environments. Also offers excellent protection for water-based fluids.

Features/Benefits:

- · Creates an impenetrable barrier against water droplets
- Pleated element provides a large surface area and is 99.5% efficient in blocking particles 1µ and larger
- Coalesces oil mist, preventing contamination of working environment (BB-SB-35 only)
- Visual vacuum indicator option actuates when maximum restriction has been reached
- Rugged ABS plastic housing
- · Easy installation requires hand tighten only



BB-SB-25 BB-SB-35

MODEL NUMBER	88-SB-25	BB-SB-35
Unit size (height x dia., in.)	5 x 5	5 x 5
Filtration area (square in.)	180	180
Max. flow rate (cfm @ 1 psid)	40	40
Beta rating	β1 = 200 (99.5% efficient at 1μ)	$\beta 1 = 200 \ (99.5\%$ efficient at $1\mu)$
Operating temperature range (*F)	-20 to +200	-20 to +200
Filter media	ePTFE/Polyester	ePTFE/Polyester
DETECTION OF THE PARTY OF THE P	TO STATE OF THE ST	

Flange, field, and threaded adapters are available for mounting. Hand tighten only. Replace 1x/year or when indicated by vacuum indicator option.



Beach Filter Products, Inc. 7682 Glenville Rd. Glenrock, PA 17327-8809 (717) 235-1136 • Fax (717) 235-4558 1-800-BEACH-85 • (1-800-232-2485) www.beachfilters.com

Hydraulic Reservoirs

Transformers

Storage Containers

