

BEACH FILTERS *Clear The Air*

Hot Topic

New Literature Now Available

Some History

In 1968, Willard C. Beach moved his desiccant filtration and horse racing harness businesses from New Jersey to Glensville, PA into a plumbing supply company building.

In 1984, Beach Precision Parts Company is incorporated as Beach Filter Products, Inc., a women owned Sub-S corporation.

In 2000, Beach Filters partners with Des-Case Corporation as a Master Distributor of its hydraulic oil reservoir breather and oil filtration products.

In 2007, Beach opened a second plant in nearby Hanover, PA and installed a proprietary auto-sew line for low cost production of large desiccant bags.

In 2014, Beach consolidated the Glensville headquarters and filter assembly plant into its Hanover facility.

Beach Filter Products New Address!



WE MOVED

After 50 years in Glensville, PA, Beach Filters has closed this plant effective March 1, 2014. Our three businesses have now consolidated into the new Hanover, PA facility.

Our new addresses are:

Mailing:
PO BOX 505
Hanover, PA 17331

Shipping:
555 Centennial Ave
Hanover, PA 17331

Our phone numbers remain the same:

717-235-1136

800-232-2485

Fax:

717-235-4858

In-Line Filtration Line: Continues to Fit Customer Requirements

Point-of-Use desiccant filtration prevents problems in compressed air.

While many of our customers have moved to the triple action T-line filters, the original Beach In-Line single action filters continue to meet customer requirements.

Beach In-line desiccant filters offer dependable performance and good value.

Dual Replaceable Elements

All models feature dual element design which allow users to combine clay, silica gel and charcoal elements to customize their filtration in a single housing.

Full Flow Rate Range

In-line filters are available in the higher flow applications such as 100, 200 and 1200 scfm models.

Full range includes 20, 60, 100, 200 and 1200 models

Three Housing Options

Clear Acrylic, 150 psi max pressure • All aluminum, 250 psi max pressure
aluminum w/sight-glass, 250 psi max pressure



Model Numbers

F-65 F-600
F-125 1200W
F-300

Cylform Desiccant Element

Airflow

Bottom Spacer



Top Spacer

Particulate Disc

Standard Desiccant
Removes Oil, Vapor
& Moisture

Sump

Drain Petcock

[CLICK HERE
FOR ANIMATED
DIAGRAM](#)

 **Forward To A Friend**



The Clear Choice for Point-of-Use
Compressed Air & Oil Filtration

Mailing: PO Box 505, Hanover, PA 17331 • Shipping: 555 Centennial Ave., Hanover, PA 17331
(717) 235-1136 • FAX (717) 235-4858

1-800-232-2485 • beachfilters.com • sales@beachfilters.com